


**X-heavy duty Hollow shaft encoder, Incremental**

- Performance hollow shaft encoder for heavy duty industries
- Hybrid bearings for extended lifetime
- High vibration and shock resistance
- Electrically insulated shaft; up to 2,5 kV

**Mechanical data**


Operating temperature	-40 °C...+85 °C
Ingress protection class [IEC 60529]	IP67 (IP66 at shaft inlet)
Vibration [IEC 60068-2-64]	≤ 20 g, 55-2000 Hz
Shock [IEC 60068-2-27]	≤ 400 g, 3.5 ms
Shaft load max (axial/radial)	100 N / 300 N
Rotational speed max	6000 rpm
Shaft material	Stainless steel with insulated hybrid bearings
Cover material	Aluminium (anodized)
Weight	1400 g

Encoder configuration



Type	XHI
Model	801 Extra robust
Shaft type	Ø12 mm blind hollow shaft
Flange type	86-flange
Resolution	2500 ppr
Power supply	9-30 Vdc
Output signal	HTL with additional optolink output
Connection type	M23 connector 12-pin +ST connector
Connecting direction	Radial
Pin layout	CW
Number of channels	6 (S00, S00\, S90, S90\, Sref, Sref\)
Torque support	120° torque bracket

Electrical data

Polarity protected	Yes
Short circuit protected incremental outputs	Yes
Current consumption (No load)	60 mA at 24 Vdc (Max. 80 mA)
Incremental output load (max)	± 40 mA
Output frequency max	200 kHz
Cable length max	100 m at 100 kHz (Fiber length 2700 m)
Channel separation	90 °el ± 25 °el
Dividing error	± 50 °el

Dimensions**Pin Configuration**

Function	Pin
S00	5
S00 inverted	6
S90	8
S90 inverted	1
Sref	3
Sref inverted	4
+E Volt	12
0 Volt	10
Status	7
Shield	Case
ST connector	
Optolink	Fiber

**Output signal****Available options**

Overvoltage protection

Advanced Diagnostic System

Order information

Part number 737336-01